

Three-point gripper HGDD-80-A

Part number: 1163049

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|---|--|
| Size | 80 |
| Stroke per gripper jaws | 12 mm |
| Max. replacement accuracy | ≤0.2 mm |
| Max. angular gripper jaw backlash ax, ay | ≤0.1 deg |
| Max. gripper jaw backlash Sz | ≤0.05 mm |
| Rotationally symmetrical | ≤0.2 mm |
| Repetition accuracy, gripper | ≤0.05 mm |
| Number of gripper jaws | 3 |
| Mounting position | optional |
| Mode of operation | Double-acting |
| Gripper function | 3-point |
| Design | Force pilot operated motion sequence |
| Position detection | Via proximity switch |
| Symbol | 00991894 |
| Total gripping force, opening, 0.6MPa (6bar, 87 psi) | 2829 N |
| Total gripping force, closing, 0.6MPa (6bar, 87 psi) | 2745 N |
| Operating pressure | 3 bar ... 8 bar |
| Operating pressure of blocked air | 0 bar ... 0.5 bar |
| Max. operating frequency of gripper | ≤4 Hz |
| Min. opening time at 0.6 MPa (6 bar, 87 psi) | 152 ms |
| Min. closing time at 0.6 MPa (6 bar, 87 psi) | 142 ms |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Degree of protection | IP65 |
| Ambient temperature | 5 °C ... 60 °C |
| Gripper force per gripper jaw, opening, 0.6 MPa (6 bar, 87 psi) | 943 N |
| Gripper force per gripper jaw, closing, 0.6 MPa (6 bar, 87 psi) | 915 N |
| Mass moment of inertia | 70.22 kgcm ² |
| Max. force on gripper jaw Fz static | 3600 N |
| Max. torque at gripper Mx static | 100 Nm |
| Max. torque at gripper My static | 65 Nm |
| Max. torque at gripper Mz static | 75 Nm |

| Feature | Value |
|---|--|
| Lubrication interval for guide components | 5 MioCyc |
| Max. mass per external gripper finger | 790 g |
| Product weight | 3522 g |
| Type of mounting | Either: Via through-hole and dowel pin Via female thread and dowel pin |
| Pneumatic connection, blocked air | G1/8 |
| Pneumatic connection | G1/8 |
| Note on materials | RoHS-compliant |
| Material cover cap | High-alloy stainless steel |
| Material housing | Smooth-anodised wrought aluminium alloy |
| Material gripper jaws | Hardened steel |