

**Clevis foot**  
**CRLNG-32**  
Part number: 161840



 [General operating condition](#)

**Data sheet**

| Feature                                            | Value                                                                                                                                                    |
|----------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size                                               | 32                                                                                                                                                       |
| Based on standard                                  | ISO 15552 (previously also VDMA 24562, ISO 6431, NF E49 003.1, UNI 10290)                                                                                |
| Mounting position                                  | optional                                                                                                                                                 |
| Corrosion resistance class CRC                     | 4 - Very high corrosion stress                                                                                                                           |
| LABS (PWIS) conformity                             | VDMA24364-B2-L                                                                                                                                           |
| Suitability for the production of Li-ion batteries | Suitable for battery production according to the Festo internal definition of the degree of severity F1A with restrictions regarding the use of Cu/Zn/Ni |
| Ambient temperature                                | -40 °C ... 80 °C                                                                                                                                         |
| Max. load capacity                                 | 0.9 kN                                                                                                                                                   |
| Product weight                                     | 133 g                                                                                                                                                    |
| Note on materials                                  | RoHS-compliant                                                                                                                                           |
| Material mounting                                  | Electropolished<br>High-alloy steel                                                                                                                      |
| Material bearing                                   | Polymer                                                                                                                                                  |