

Suction cup without connector ESV-20-BS

Part number: 191056

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|---|---|
| Height compensator for suction cup | 6 mm |
| Min. workpiece radius | 40 mm |
| Suction cup diameter | 20 mm |
| Suction cup volume | 1.6 cm ³ |
| Position of connection | Top |
| Mounting position | optional |
| Symbol | 00991485 |
| Suction cup shape | Round bellows 1.5 convolutions |
| Operating pressure | -0.095 MPa ... 0 MPa |
| Operating pressure | -0.95 bar ... 0 bar |
| Operating pressure | -13.775 psi ... 0 psi |
| Nominal operating pressure | -0.07 MPa |
| Nominal operating pressure | -0.7 bar |
| Nominal operating pressure | -10.15 psi |
| Operating medium | Atmospheric air based on ISO 8573-1:2010 [7::-] |
| LABS (PWIS) conformity | VDMA24364 zone III |
| Suitable for use with food | See supplementary material information |
| Ambient temperature | -30 °C ... 180 °C |
| Holding force at nominal operating pressure | 12.9 N |
| Product weight | 1.9 g |
| Colour | Transparent |
| Shore hardness | 50 +/- 5 |
| Note on materials | RoHS-compliant |
| Material suction cup | VMQ (silicone) |