



# Filter LF-D-5M-MINI

Part number: 192557

FESTO



 General operating condition

## Data sheet

| Feature                        | Value  |
|--------------------------------|--|
| Size                           | Mini   |
| Series                         | D  |
| Mounting position              | Vertical +/-5°   |
| Grade of filtration            | 5 µm   |
| Condensate drain               | Manually rotating  |
| Design                         | Sintered filter with centrifugal separator               |
| Bowl guard                     | Metal bowl guard   |
| Symbol                         | 00991519   |
| Operating pressure             | 0 bar ... 16 bar   |
| Operating medium               | Compressed air to ISO 8573-1:2010 [-:9:-]<br>Inert gases |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress                            |
| LABS (PWIS) conformity         | VDMA24364-B1/B2-L  |
| Air purity class at output     | Compressed air to ISO 8573-1:2010 [6:8:4]<br>Inert gases |
| Media temperature              | -10 °C ... 60 °C   |
| Ambient temperature            | -10 °C ... 60 °C   |
| Product weight                 | 250 g  |
| Type of mounting               | In-line installation<br>With accessories                 |
| Pneumatic connection, port 1   | Sub-base   |
| Pneumatic connection, port 2   | Sub-base   |
| Note on materials              | RoHS-compliant   |
| Material filter                | PE   |
| Material housing               | Die-cast zinc  |
| Material bowl                  | PC   |