


Pinch valve

VZQA-C-M22U-15-GG-ALV4N-4

Part number: 3022831

FESTO



[PDF](#) [General operating condition](#)

Data sheet

| Feature | Value |
|-----------------------------|---|
| Design | Pinch valve, pneumatically actuated |
| Type of actuation | Pneumatic |
| Sealing principle | Soft |
| Mounting position | optional |
| Type of mounting | In-line installation |
| Connection Process valve | G1/2 |
| Nominal size DN | 15 |
| Valve function | 2/2 open, monostable |
| Flow direction | Reversible |
| Medium pressure | 0 MPa ... 0.4 MPa |
| Medium pressure | 0 bar ... 4 bar |
| Medium pressure | 0 psi ... 58 psi |
| Note on the medium pressure | Use in the vacuum range was tested up to -0.09 MPa with the air at room temperature. Depending on the application, a counter-vacuum may have to be created on the control side to guarantee the media flow. |
| Operating pressure | 0.1 MPa ... 0.65 MPa |
| Operating pressure | 1 bar ... 6.5 bar |
| Operating pressure | 14.5 psi ... 94.25 psi |
| Nominal pressure PN | 10 |
| Differential pressure | 0.25 MPa |
| Differential pressure | 2.5 bar |
| Differential pressure | 36.25 psi |
| Burst pressure | 1.6 MPa |
| Burst pressure | 16 bar |
| Burst pressure | 232 psi |
| Overload pressure | 0.78 MPa |
| Overload pressure | 7.8 bar |
| Overload pressure | 113.1 psi |
| Type of reset | Rebound resilience |
| Type of piloting | Externally controlled |

| Feature | Value |
|--|---|
| Auxiliary pilot air port 12 | G1/8 |
| Pilot medium | Compressed air to ISO 8573-1:2010 [7:4:4] |
| Symbol | 00995245 |
| Medium | Compressed air to ISO 8573-1:2010 [-::-] |
| Max. viscosity | 4000 mm ² /s |
| Media temperature | -5 °C ... 60 °C |
| Ambient temperature | -5 °C ... 60 °C |
| Storage temperature | 5 °C ... 20 °C |
| Flow rate Kv | 5 m ³ /h |
| Switching time on | 250 ms |
| Switching time off | 250 ms |
| Note on materials | RoHS-compliant |
| LABS (PWIS) conformity | VDMA24364 zone III |
| Suitability for the production of Li-ion batteries | Suitable for battery production according to the Festo internal definition of the degree of severity F1A with restrictions regarding the use of Cu/ Zn/Ni |
| Material housing | Wrought aluminium alloy |
| Material housing cover | High-alloy stainless steel |
| Material seals | FPM |
| Material shut-off element | NBR |
| Product weight | 265 g |
| Material bowl | PA6 |