



AND block ZK-PK-3-6/3

Part number: 4204

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|---|--|
| Valve function | AND function |
| Pneumatic connection, port 1 | PK-3 |
| Pneumatic connection, port 2 | PK-3 |
| Type of mounting | Front panel mounting |
| Standard nominal flow rate (standardised to DIN 1343) | 100 l/min |
| Operating pressure | 1.6 bar ... 8 bar |
| Ambient temperature | -10 °C ... 60 °C |
| Material housing | POM |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:-:-] |
| Explosion protection | The information in the certificate must be observed! Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX) |
| Nominal size | 2.5 mm |
| Mounting position | optional |
| Symbol | 00991462 |
| Note on operating and pilot medium | Lubricated operation possible (in which case lubricated operation will always be required) |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Media temperature | -10 °C ... 60 °C |
| Product weight | 85 g |
| Pneumatic connection, port 3 | PK-3 |
| Material seals | NBR |