


# Mounting kit SMBR-8-8/100-S6

Part number: 538937

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                            | Value                                                                                                                                                                                                                             |
|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size                                               | 8                                                                                                                                                                                                                                 |
| Design                                             | For T-slot                                                                                                                                                                                                                        |
| Mounting position                                  | optional                                                                                                                                                                                                                          |
| For piston diameter                                | Ø8 - Ø100                                                                                                                                                                                                                         |
| Corrosion resistance class CRC                     | 4 - Very high corrosion stress                                                                                                                                                                                                    |
| LABS (PWIS) conformity                             | VDMA24364-B2-L                                                                                                                                                                                                                    |
| Suitability for the production of Li-ion batteries | Metals with more than 5% by mass of copper, zinc or nickel by mass are excluded from use. Exceptions are nickel in steel, chemically nickel-plated surfaces, printed circuit boards, cables, electrical plug connectors and coils |
| Ambient temperature                                | -20 °C ... 120 °C                                                                                                                                                                                                                 |
| Product weight                                     | 20 g                                                                                                                                                                                                                              |
| Note on materials                                  | RoHS-compliant                                                                                                                                                                                                                    |
| Material housing                                   | Anodised<br>High-alloy stainless steel                                                                                                                                                                                            |
| Material screws                                    | High-alloy stainless steel                                                                                                                                                                                                        |