


Proximity sensor SMT-8M-A-PS-24V-E-2,5-OE

Part number: 574335

FESTO



 [General operating condition](#)

Data sheet

| Feature | Value |
|--|---|
| Design | For T-slot |
| Based on standard | EN 60947-5-2 |
| Symbol | 00991152 |
| Approval | RCM trademark c UL us listed (OL) |
| CE mark (see declaration of conformity) | To EU EMC Directive In accordance with EU RoHS Directive |
| UKCA marking (see declaration of conformity) | To UK instructions for EMC To UK RoHS instructions |
| Certificate issuing authority | UL E232949 |
| Special characteristics | Oil resistant |
| Note on materials | RoHS-compliant Free of halogen |
| Instructions on use | https://www.festo.com/Drive-Sensor-Overview |
| Measured variable | Position |
| Measuring principle | Magneto-resistive |
| Ambient temperature | -40 °C ... 85 °C |
| Repetition accuracy | 0.2 mm |
| Switching output | PNP |
| Switching element function | N/O contact |
| Switch-on time | ≤1.3 ms |
| Switch-off time | ≤7.3 ms |
| Max. switching frequency | 130 Hz |
| Max. output current | 100 mA |
| Max. output current using mounting kits | 100 mA |
| Max. switching capacity DC | 2.8 W |
| Max. switching capacity DC using mounting kits | 2.8 W |
| Voltage drop | <1.5 V |
| Short circuit current rating | yes |
| Overload protection | Available |
| Rated operational voltage DC | 24 V |
| Operational voltage range DC | 5 V ... 30 V |
| Reverse polarity protection | For all electrical connections |
| Electrical connection 1, connection type | Cable |
| Electrical connection 1, connector system | Open end |
| Electrical connection 1, number of connections/cores | 3 |
| Connection outlet orientation | In-line |

| Feature | Value |
|--|--|
| Test conditions cable | Test conditions on request Torsional strength: > 300,000 cycles, ±270°/0.1 m Flexural strength: >50000 cycles, bending radius 5 mm Energy chain: > 5 million cycles, bending radius 28 mm |
| Cable length | 2.5 m |
| Cable characteristic | Suitable for energy chains/robot applications |
| Cable sheath colour | Grey |
| Material cable sheath | TPE-U(PUR) |
| Material insulating sheath | PP |
| Wire ends | Wire ferrule |
| Type of mounting | Screw-clamped Insertable in the slot from above |
| Max. tightening torque | 0.6 Nm |
| Mounting position | optional |
| Product weight | 29.1 g |
| Housing colour | Black |
| Material housing | High-alloy stainless steel |
| Switching status indication | Yellow LED |
| Function reserve indication | Orange LED |
| Ambient temperature with moving cable | -20 °C ... 85 °C |
| Degree of protection | IP65 IP68 IP69K |
| LABS (PWIS) conformity | VDMA24364-B2-L |
| Suitability for the production of Li-ion batteries | Suitable for battery production according to the Festo internal definition of the degree of severity F1A with restrictions regarding the use of Cu/ Zn/Ni |
| Cleanroom class | Element installed statically, no meaningful evaluation possible according to ISO 14644-1 |