


# Pressure sensor SPAW-P2R-G14F-2P-M12

Part number: 8022742

FESTO



[PDF](#) General operating condition

## Data sheet

| Feature  | Value  |
|--|--|
| Symbol   | 00991165   |
| Approval   | RCM trademark<br>c UL us listed (OL)                                       |
| CE mark (see declaration of conformity)              | To EU EMC Directive<br>In accordance with EU RoHS Directive                |
| UKCA marking (see declaration of conformity)         | To UK instructions for EMC<br>To UK RoHS instructions                      |
| Note on materials                                    | RoHS-compliant   |
| Measured variable                                    | Relative pressure  |
| Measurement method                                   | Piezoresistive pressure sensor   |
| Start value for pressure measuring range             | 0 MPa  |
| Start value for pressure measuring range             | 0 bar  |
| Start value for pressure measuring range             | 0 psi  |
| End value for pressure measuring range               | 0.2 MPa  |
| End value for pressure measuring range               | 2 bar  |
| End value for pressure measuring range               | 29 psi   |
| Overload pressure                                    | 0.4 MPa  |
| Overload pressure                                    | 4 bar  |
| Overload pressure                                    | 58 psi   |
| Operating medium                                     | Compressed air to ISO 8573-1:2010 [-:-:-]<br>Liquid media<br>Gaseous media |
| Media temperature                                    | -20 °C ... 85 °C   |
| Ambient temperature                                  | 0 °C ... 80 °C   |
| Accuracy in ± % FS                                   | 1 %FS  |
| Repetition accuracy in ± %FS                         | 0.15 %FS   |
| Switching output                                     | 2xPNP  |
| Switching function                                   | Freely programmable  |
| Switching element function                           | Switchable   |
| Max. output current                                  | 250 mA   |
| Rise time  | 3 ms   |
| Short circuit current rating                         | yes  |
| Operational voltage range DC                         | 15 V ... 35 V  |
| Reverse polarity protection                          | For operating voltage  |
| Electrical connection 1, connection type             | Plugs  |
| Electrical connection 1, connector system            | M12x1, A-coded to EN 61076-2-101   |
| Electrical connection 1, number of connections/cores | 4  |

| Feature  | Value  |
|--|--|
| Electrical connection 1, type of mounting            | Screw-type lock<br>Not rotatable               |
| Electrical connection 1, compatible type of mounting | Compatible with rotatable screw-type lock      |
| Electrical connection 1, connection pattern          | 00995386                                       |
| Type of mounting                                     | Via female thread<br>With accessories          |
| Mounting position                                    | optional                                       |
| Pneumatic connection                                 | Female thread G1/4                             |
| Product weight                                       | 230 g  |
| Material housing                                     | High-alloy stainless steel                     |
| Material in contact with the medium                  | High-alloy stainless steel                     |
| Display type   | 4-place alphanumeric<br>LED indicator          |
| Displayable units                                    | MPa<br>bar<br>kPa<br>kg/cm <sup>2</sup><br>psi |
| Switching status indication                          | Red LED  |
| Setting options                                      | Via display and keys                           |
| Protection against tampering                         | PIN code                                       |
| Setting range threshold value                        | 0.5 % ... 100 %                                |
| Setting range hysteresis                             | 0.5 % ... 99.5 %                               |
| Degree of protection                                 | IP65<br>IP67                                   |
| Corrosion resistance class CRC                       | 4 - Very high corrosion stress                 |
| LABS (PWIS) conformity                               | VDMA24364 zone III                             |