












Series 200 Pneumatic command

Valves "Tecno228"
3/2-5/2-5/3-G 1/8"

Pneumatic-Spring			3/2	Ordering code	5/2	Pneumatic-Spring		
				T228.t .11.1				
				TYPE				
				32 = 3 ways				
				52 = 5 ways				
				t				

Pneumatic-Differential (external)			3/2	Ordering code	5/2	Pneumatic-Differential (external)		
 			T228.t .11.12 TYPE 32 = 3 ways 52 = 5 ways			 		
Weight gr. 74 Minimum operating pressure 2,5 bar								
Operational characteristics	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working ports size	Pilot ports size
	Filtered air, with or without lubri-	10 bar	Min. -5°C Max. +50°C					

Pneumatic-Differential self-feeding			3/2	Ordering code	5/2	Pneumatic-Differential self-feeding					
				T228.t .11.12/1							
										TYPE	
										32 = 3 ways	
										52 = 5 ways	
											
Weight gr. 70 Minimum operating pressure 2,5 bar											
Operational characteristics	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working ports size	Pilot ports size			
	Filtered air, with or without lubri-	10 bar	Min. -5°C	Max. +50°C							